

ROPES & MOORING LIROS DOCK AND ANCHOR LINES

Liros Handy Elastic

Superior quality, soft, easy handling and easy splicing dock and anchor line. High breaking strength, high-stretch (<20%), extremely abrasion resistant, is perfect also for towing and can be used even without shock absorbers. High-elastic braided Polyamide core. High-tenacity UV resistant Polyamide cover. Non Floating.
daN= breaking strength in Kg



Cod.	ø mm	Colour	daN	m	UM	€
3102808200	8	BLUE NAVY	1600	200	PCK	
3102810200	10	BLUE NAVY	2500	200	PCK	
3102812200	12	BLUE NAVY	3900	200	PCK	
3102814150	14	BLUE NAVY	4800	150	PCK	
3102816100	16	BLUE NAVY	6000	100	PCK	
3102818100	18	BLUE NAVY	8500	100	PCK	
3102820100	20	BLUE NAVY	9900	100	PCK	
3102822100	22	BLUE NAVY	10600	100	PCK	
3102824100	24	BLUE NAVY	12000	100	PCK	
3102908200	8	BLACK	1600	200	PCK	
3102910200	10	BLACK	2500	200	PCK	
3102912200	12	BLACK	3900	200	PCK	
3102914150	14	BLACK	4800	150	PCK	
3102916100	16	BLACK	6000	100	PCK	
3102918100	18	BLACK	8500	100	PCK	
3102920100	20	BLACK	9900	100	PCK	
3102922100	22	BLACK	10600	100	PCK	
3102924100	24	BLACK	12000	100	PCK	



Liros Porto

Superior quality extremely abrasion resistant, very easy handling and easy splicing dock and anchor line. Compact and high strength line, will not stiffen up in time. High-tenacity braided Poliester core. UV resistant high-twisted Poliester cover. Working stretch <15%. Non floating.
daN= breaking strength in Kg



Cod.	ø mm	Colour	daN	m	UM	€
3102510200	10	BLUE NAVY	2300	200	PCK	
3102512200	12	BLUE NAVY	2900	200	PCK	
3102514150	14	BLUE NAVY	3700	150	PCK	
3102516100	16	BLUE NAVY	4900	100	PCK	
3102518100	18	BLUE NAVY	5300	100	PCK	
3102520100	20	BLUE NAVY	6300	100	PCK	
3102522100	22	BLUE NAVY	8900	100	PCK	
3102524100	24	BLUE NAVY	9600	100	PCK	
3102410200	10	BLACK	2300	200	PCK	
3102412200	12	BLACK	2900	200	PCK	
3102414150	14	BLACK	3700	150	PCK	
3102416100	16	BLACK	4900	100	PCK	
3102418100	18	BLACK	5300	100	PCK	
3102420100	20	BLACK	6300	100	PCK	
3102422100	22	BLACK	8900	100	PCK	
3102424100	24	BLACK	9600	100	PCK	



NEW

Liros Super Yacht Mooring

Dock and anchor line for superyachts up to 90 meters. The flexible high-tenacity braided Polyester core provides the best in safety, while the 24 plaited Polyester cover delivers premium comfort, easy handling and easy splicing. Working stretch <15%. Non floating.
daN= breaking strength in Kg



Cod.	ø mm	Colour	daN	Boat Size m	m	UM	€
3100824100	24	BLUE NAVY	11500	Up to 30	100	PCK	
3100828100	28	BLUE NAVY	15900	Up to 40	100	PCK	
3100832100	32	BLUE NAVY	19800	Up to 50	100	PCK	
3100836100	36	BLUE NAVY	26000	Up to 60	100	PCK	
3100840100	40	BLUE NAVY	32800	Up to 65	100	PCK	
3100844100	44	BLUE NAVY	38500	Up to 70	100	PCK	
3100848100	48	BLUE NAVY	46000	Up to 80	100	PCK	
3100852100	52	BLUE NAVY	53500	Up to 90	100	PCK	
3100924100	24	BLACK	11500	Up to 30	100	PCK	
3100928100	28	BLACK	15900	Up to 40	100	PCK	
3100932100	32	BLACK	19800	Up to 50	100	PCK	
3100936100	36	BLACK	26000	Up to 60	100	PCK	
3100940100	40	BLACK	32800	Up to 65	100	PCK	
3100944100	44	BLACK	38500	Up to 70	100	PCK	
3100948100	48	BLACK	46000	Up to 80	100	PCK	
3100952100	52	BLACK	53500	Up to 90	100	PCK	

