

AIR VENTS ELECTRIC FANS AND EXTRACTORS

Turbo In-Line 2T Blower

Turbo in-line bilge blower for engine rooms, galleys and cabins. Amp draw 2,9A (12V).

Cod.	V	Intake ø mm	L mm	UM	€
1710010	12	75	130	PCS	
1710012	12	100	130	PCS	
1710011	24	100	130	PCS	



Turbo In-Line Attwood Blowers

Turbo in-line waterproof blowers for engine rooms and cabins. Complete with 2 tie straps. Blowers designed to grant 25% more air flux than other blowers, using 40% less power. Nickel-plated motor with cap and sealed wiring for total corrosion protection.

Cod.	Ref	V	Intake ø mm	L mm	UM	€
1710015	Turbo 3000	12	75	130	PCS	
1710017	Turbo 4000	12	100	130	PCS	
1710018	Turbo 4000	24	100	130	PCS	



HD In-Line 1000F Blowers


Heavy duty in-line electric continuous duty blowers. Designed with aerospace technology, very silent. Air flux 1000 m3/h guaranteed.

Cod.	V	Capacity m3 per Hour	Intake ø mm	L mm	UM	€
1710087	12	1000	178	160	PCS	
1710088	24	1000	178	160	PCS	



Flanged Blowers


High quality continuous duty flanged centrifugal blowers for engine rooms and bilges. Reinforced ABS case and waterproof motor. Wall flange mount. CE certified complying ISO 9097 Marine/ISO 8846/ISO 10133/EN 55014 standards and N.M.M.A USCG 183.410 rules.



Cod.	V	Capacity m³ per Hour	H x W x L mm	Ports ø mm	UM	€
1710013	12	280	200 x 165 x 195	In:75 - Out: 72	PCS	
1710024	24	280	200 x 165 x 195	In:75 - Out: 72	PCS	

Flanged Heavy Duty Blowers


High quality continuous and Heavy Duty flanged centrifugal blowers for engine rooms and bilges. Reinforced ABS case and waterproof motor. Wall flange mount. CE certified complying ISO 9097 Marine/ISO 8846/ISO 10133/EN 55014 standards and N.M.M.A USCG 183.410 rules.



Cod.	V	Capacity m³ per Hour	H x W x L mm	Ports ø mm	UM	€
1710055	12	550	290 x 257 x 150	In:110 - Out:103	PCS	
1710056	24	550	290 x 257 x 150	In:110 - Out:103	PCS	
1710057	12	750	290 x 257 x 150	In:150 - Out:103	PCS	
1710058	24	750	290 x 257 x 150	In:150 - Out:103	PCS	
1710061	24	1000	290 x 257 x 180	In:150 - Out:103	PCS	

Bracket Blowers

High quality continuous duty bracket mount centrifugal blowers for engine rooms and bilges. Reinforced ABS case and waterproof motor. Bracket base mount. CE certified complying ISO 9097 Marine/ISO 8846/ISO 10133/EN 55014 standards and N.M.M.A USCG 183.410 rules.



Cod.	V	Capacity m³ per Hour	H x W x L mm	Ports ø mm	UM	€
1710075	12	550	290 x 257 x 150	In:100 - Out:110	PCS	
1710076	24	550	290 x 257 x 150	In:100 - Out:110	PCS	
1710077	12	750	290 x 257 x 150	In:150 - Out:103	PCS	
1710078	24	750	290 x 257 x 150	In:150 - Out:103	PCS	
1710081	24	1000	290 x 257 x 180	In:150 - Out:103	PCS	